

TITAN - TITAN GT

TITAN TECHNICAL DATA SHEET

MODEL		TITAN 100kVA	TITAN 125kVA	TITAN 160kVA	TITAN 200kVA	TITAN 250kVA	TITAN 300kVA	TITAN 400kVA	TITAN 500kVA	
POWER	kVA	100	125	160	200	250	300	400	500	
	kW	100	125	160	200	250	300	400	500	
INPUT	Rated voltage	400 Vac three-phase with neutral								
	Voltage tolerance	-20% to +15%								
	Rated frequency	45 to 65 Hz								
	Power factor	>0.99								
	Current distortion (THDi)	<3%								
OUTPUT	Rated voltage	380/400/415 Vac three-phase with neutral								
	Voltage stability	±1% (static)								
	Frequency	50/60 Hz								
	Frequency stability	±0.001 (free running)								
	Power factor	1								
	Crest factor	3:1								
	Voltage distortion	<1% with linear load, <5% with distorting load								
	Permissible overload*	125% for 10 minutes, 150% for 30 seconds			125% for 5 minutes, 150% for 30 seconds					
BATTERY	Number per string (12V)	60 – 62 configurable								
	Max. charging current	Up to 50 A			Up to 120 A					
	Common batteries for parallel configuration	Supported								
EFFICIENCY	VFI mode	Up to 96%								
	ECO mode	Up to 98%								
BYPASS	Rated voltage	380/400/415 Vac three-phase with neutral								
	Voltage tolerance	±10% (selectable)								
	Frequency	50/60 Hz (selectable)								
	Frequency tolerance	±10 Hz (selectable)								
GENERAL	Parallel connection	Up to 6 units								
	Dimensions (WxDxH) mm	560x940x1800			880x970x1978			1430x970x1978		
	Weight (kg)	320	360	380	720	850	930	1080	1250	
	Protection class	IP20								
CONNECTIVITY	User interface	LCD display, LED synoptics and keyboard			Colour touch screen display					
	Built-in communication ports	USB, RS232, EPO, auxiliary contact for battery switch, auxiliary contact for external manual bypass, diesel mode contact and two additional slots for optional cards.								
	Optional accessories	Cards: SNMP, RS485, ModBus, dry relay contacts, remote monitoring panel.								
ENVIRONMENTAL PARAMETERS	Operating temperature**	0 – 40°C								
	Relative humidity	0 – 95% (without condensing)								
	Altitude (a.s.l.)	<1000 m with no power derating, >1000 m with 0.5% derating for every 100 m.								
	Audible noise at 1 m.	<60 dBA								
REGULATIONS	Standards	IEC EN 62040-1, IEC EN 62040-2, IEC EN 62040-3								
	Marking	CE, UKCA								

* Subject to conditions ** To be verified according to the battery parameters

TITAN - TITAN GT

TITAN GT TECHNICAL DATA SHEET

MODEL		TITAN GT 100-125-160 kVA	TITAN GT 200-250-300 kVA	TITAN GT 400kVA	TITAN GT 500kVA	TITAN GT 600kVA	TITAN GT 800kVA
POWER	kVA	100 / 125 / 160	200 / 250 / 300	400	500	600	800
	kW	90 / 112.5 / 144	180 / 225 / 270	360	450	540	720
INPUT	Rated voltage	400 Vac three-phase with neutral					
	Voltage tolerance	-20% to +15%					
	Rated frequency	45 to 65 Hz					
	Power factor	0.99					
	Current distortion (THDi)	<3%					
OUTPUT	Rated voltage	380/400/415 Vac three-phase with neutral					
	Voltage stability	±1% (static)					
	Frequency	50/60 Hz					
	Frequency stability	±0.001 (free running)					
	Power factor	0.9					
	Crest factor	3:1					
	Voltage distortion	<1% with linear load, <5% with distorting load					
	Permissible overload	125% for 10 minutes, 150% for 1 minute					
BATTERY	Number per string (12V)	50/52 configurable					
	Max. charging current *	Up to 100 A					Up to 200 A
EFFICIENCY	VFI mode	Up to 95%					
	ECO mode	Up to 98%					
BYPASS	Rated voltage	380/400/415 Vac three-phase with neutral					
	Voltage tolerance	±10% (selectable)					
	Rated frequency	50/60 Hz (selectable)					
	Frequency tolerance	±10 Hz (selectable)					
GENERAL	Parallel connection	Up to 6 units					
	Dimensions (WxDxH) mm	815x825x1670	1200x860x1900	1990x990x1920	2430x990x2020	2440x990x2020	3640x990x1920
	Weight (kg)	100 kVA = 625 125 kVA = 660 160 kVA = 715	200 kVA = 970 250 kVA = 1090 300 kVA = 1170	1820	2220	2400	3600
	Protection class	IP20					
CONNECTIVITY	User interface	LCD display, LED synoptics and keyboard					
	Built-in communication ports	USB, RS232, EPO, auxiliary contact for battery switch, auxiliary contact for external manual bypass, diesel mode contact and two additional slots for optional cards.					
	Optional accessories	Cards: SNMP, RS485, ModBus, dry relay contacts, remote monitoring panel.					
ENVIRONMENTAL PARAMETERS	Operating temperature**	0 – 40°C					
	Relative humidity	0 – 95% (without condensing)					
	Altitude (a.s.l.)	<1000 m with no power derating, >1000 m with 0.5% derating for every 100 m.					
	Audible noise at 1 m.	<62 dBA					
REGULATIONS	Standards	IEC EN 62040-1, IEC EN 62040-2, IEC EN 62040-3					
	Marking	CE, UKCA					

* Subject to conditions ** To be verified according to the battery parameters